

MANIFATTURA TUBI GOMMA S.p.A.

 Grisignano di Zocco, 36040 (VI) ITALY
 T. +39 0444.614755 | info@mtgspa.com
 www.mtgspa.com


APPLICATION

- Multipurpose hose "Full Ohm", designed for conveying cosmetic, pharmaceutical and highly flammable chemical products in working areas requiring utmost safety.
- Execution complying with EN 12115: 2011.
- Engineered to ensure dissipation of electrostatic charges not only on the surface, but also through the hose wall: electrical resistance through the hose wall: $R < 10^9$ Ohm.

CONSTRUCTION

TUBE

- PFA (Perfluoroalkoxy Polymer, code PFA), fully fluorinated, mirror-smooth, black colour, antistatic ($R < 10^6$ Ohm), patented.
- Compliance: USP Class VI, FDA Standards, ISO 10993 and Regulation EU n. 10/2011.

REINFORCEMENT

- High strength plies of synthetic cord.
- Embedded steel helix wire.
- Copper wires on request.

COVER

- Marble finish (UPE), black and white, patented, smooth; it resists to abrasion, ozone and weather. The special marble finish with a low coefficient of friction complies with FDA, it is odourless and tasteless and does not stain the contact surfaces.
- Antistatic: Electrical resistance $R < 10^6$ Ohm.

PATENTS

- E.P. 1450092, E.P. 1580475.
- U.S. Patent 7,389,799.

SAFETY FACTOR

- ≥ 4 times working pressure.

MAIN BENEFITS

- The perfluorinated inner liner ensures utmost chemical and temperature resistance, an excellent impermeability and absolutely hygienic and contamination-free transport of the fluid.
- The marble finish cover, smooth and easy to wash with any cleaning processes, withstands incidental contact even with aggressive chemicals conveyed inside the hose.
- Hose in accordance with EC 1935/2004 and 2023/2006/EC (GMP).
- The MTG production cycle is free from animal derived ingredients, phthalates, adipates and materials subject to restrictions acc. to EC 1907/2006 (REACH).

TEMPERATURE RANGE

- In accordance with EN 12115: 2011.

ELECTRICAL PROPERTIES

- Electrical resistance through the hose wall: $R < 10^9$ Ω .
- Identification symbol:
 - Ω/T for version without copper wires;
 - M/T for version with copper wires.

NOTE

- We suggest you to follow the instructions mentioned in the MTG "Use and maintenance guide for PFA/MFA hoses".
- Not autoclavable.

MARKING

- Embossed tape according to EN 12115: 2011, lengthwise.

TECHNICAL SPECIFICATIONS

SIZE TOLERANCES: I.D.: EN 12115 - Wall thickness: EN 12115 - Length: ISO 1307

Inner Diameter mm	Outer diameter mm	Wall thickness mm	Working pressure BAR	Burst pressure BAR	Vacuum BAR	Min. bending radius (Static) mm	Min. bending radius (Dynamic) * mm	Approx. weight kg/m	Max. length m
13	25	6.0	10	40	-0.9	135	-	0.55	20
19	31	6.0	10	40	-0.9	188	-	0.72	20
25	37	6.0	10	40	-0.9	225	-	0.89	20
32	45	6.5	10	40	-0.9	262	-	1.16	20
38	51	6.5	10	40	-0.9	338	-	1.47	20
51	65.5	7.25	10	40	-0.9	412	-	2.08	20
63.5	79.5	8.0	10	40	-0.9	450	-	2.80	20
76	92	8.0	10	40	-0.9	525	-	3.48	20
100	117	8.5	10	40	-0.9	700	-	4.70	20

 (*) In case of dynamic application please contact our Technical Dept.
 Above technical data are referring to application at room temperature (+20°C). Other sizes and colours are available upon request. Please contact our Sales Department.