



Vacuum cleaner hose, antistatic <math><10^{11}</math> Ohm

Applications

- flexible hose/ ducting for gases and for dust, powder, fibres
- industrial vacuum cleaners, vacuum cleaners
- explosion hazard area
- swimming pool cleaning
- scrubber, floor cleaning machine

Properties

- light weight
- highly flexible
- crush resistant

- floatable
- good resistance to alkalis and acids
- surface resistance <math><10^{11}</math> Ω
- in accordance with ATEX 2014/34/EU and German TRGS 727: aspiration of combustible dusts (Zone 22 inside), for conveying for non-flammable liquids, for use in zone 1 and 2 (gases), for use in Zone 0 (gases)
- conforms to RoHS guideline

Temperature Range

- 25°C to 65°C

Design, Material

EVA design

- self-supporting profile design
- open profile geometry; wall: EVA

Delivery variants

- further diameters and lengths available on request
- black (standard)

I.D. in / mm	O.D. mm	Under- pressure bar	Bending Radius mm	Weight kg/m	Dimensions in Stock m	Further Production Lengths m	Order No.
- / 20	26,8	0,500	42	0,130	-	30	373-0020-1002
1 / 25	32,2	0,500	54	0,150	30	-	373-0025-1002
- / 30	38,0	0,500	62	0,200	-	30	373-0030-1002
1,25 / 32	40,4	0,500	66	0,240	30	-	373-0032-1002
1,36 / 35	43,8	0,500	71	0,260	30	-	373-0035-1002
1,5 / 38	47,2	0,500	74	0,310	30	-	373-0038-1002
- / 40	49,4	0,500	80	0,320	30	-	373-0040-1002
1,75 / 44-45	55,0	0,500	89	0,370	30	-	373-0045-1002
2 / 50-51	60,4	0,500	97	0,440	30	-	373-0050-1002
2,36 / 60	72,0	0,500	113	0,670	30	-	373-0060-1002

Accessories



CLAMP 208



CONNECT 228



CONNECT 227

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. Additional technical data at www.norres.com. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data.