

T-155 AA
COMPRESSED AIR 20 BAR (300 PSI) - HEAVY DUTY



- TUBE :** BLACK SBR/NBR BLEND - OIL MIST RESISTANT
REINFORCEMENT : HIGH TENSILE TEXTILE CORDS
COVER : BLACK SBR - ABRASION AND OZONE RESISTANT
APPLICATION : COMPRESSED AIR DESIGNED FOR HEAVY DUTY APPLICATIONS.
TEMPERATURE : -30°C +80°C (-22°F +176°F)
BRAND TEXT : ALFAGOMMA -ITALY- T-155 20 BAR (300 PSI) AIR
BRAND TYPE : BLUE LETTERS
NOTE :
APPROVALS :
SAFETY FACTOR : <= 55mm 3:1 >= 57mm 2.5:1

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	Vac. %	BR mm	Available Length m	Stock Length m
<u>155AA019291GF0</u>	19	3/4	29	5	540	20	300			20 / 30,5 / 40	40
<u>155AA022321GF0</u>	22	7/8	32	5	610	20	300			20	20
<u>155AA025351GF0</u>	25	1	35	5	680	20	300			20 / 30,5 / 40	40
<u>155AA028381GF0</u>	28	1 1/8	38	5	780	20	300			20	20
<u>155AA030421GF0</u>	30	1 3/16	42	6	1010	20	300			20	20
<u>155AA032441GF0</u>	32	1 1/4	44	6	1060	20	300			20 / 30,5 / 40	40
<u>155AA035471GF0</u>	35	1 3/8	47	6	1140	20	300			20	20
<u>155AA038501GF0</u>	38	1 1/2	50	6	1240	20	300			20 / 30,5 / 40	40
<u>155AA040521GF0</u>	40	1 9/16	52	6	1290	20	300			20 / 40	40
<u>155AA045571GF0</u>	45	1 3/4	57	6	1440	20	300			20	20
<u>155AA051651GF0</u>	51	2	65	7	1630	20	300			20 / 30,5 / 40	40
<u>155AA055691GF0</u>	55	2 3/16	69	7	1730	20	300			30,5	30,5
<u>155AA060761GF0</u>	60	2 3/8	76	8	2160	20	300			20	20
<u>155AA063791GF0</u>	63	2 1/2	79	8	2250	20	300			20 / 30,5	20
<u>155AA076921GF0</u>	76	3	92	8	2750	20	300			20 / 30,5	20
<u>155AA090061GF0</u>	90	3 9/16	106	8	3180	20	300			20	20
<u>155AA102181GF0</u>	102	4	118	8	3600	20	300			20 / 30,5	20