

## Technical specifications

<b>Article designation:</b>	Profile "U-PIRELI" with metal reinforcement with upper seal
<b>Material:</b>	edge protector: EPDM solid rubber + sealing: EPDM-sponge rubber acc. EN45545
<b>Hardness:</b>	Edge protector: 60 +/-5 Shore A sealing: density: 0,8 +/-0,1 g/cm <sup>3</sup>
<b>Colour:</b>	black
<b>Metal carrier:</b>	steel support
<b>Operation temperature:</b>	-40°C - +100°C
<b>UV stability:</b>	good
<b>Resistance to:</b>	Alcohol, ozon, climate resistance, lyes and low acids, acetone
<b>Non resistant to:</b>	CKW, concentrated acids, aromatic hydrocarbons, oil and petrol
<b>Factory tolerance acc. to:</b>	Edge protector: DIN ISO 3302-1 E2 sealing: DIN ISO 3302-1 E3 lengths: DIN ISO 3302-1 L3

(The indications above are non-committing standard values and are to be controlled individually. If not indicated otherwise, they refer to 20°C and concentrated or saturated solutions.)

(The data refer to parts neither strained nor stressed. The indications above only allow a pre-selection, in important or extreme applications practical tests have to be performed absolutely.)