



Rubber matting

NoVibraMat

Finish: both sides ribbed (block) at an angle of 90°
 Temperature range: -20° to +80°C

Features: lightly oil-resistant • Appropriately wear-resistant and non slip

Application: vibration-damping mat • Sound isolation of devices and machines
 • Ensures a more stable position of the machine

| | | Test method |
|--------------------------------------|------|-------------|
| Specific gravity grs/cm ³ | 1,35 | DIN 53508 |
| Tensile strength Mpa | 5 | DIN 53504 |
| Elongation at break % | 300 | DIN 53504 |
| Max Load kg/cm ² | 5 | |

| Hardness (shore A +/- 5) | Thickness (mm) | Width (mtr) | Length (mtr) | Article no. |
|--------------------------|----------------|-------------|--------------|---------------|
| 45 | 8 | 0,50 | 0,50 | AV45 8/0-0,5 |
| 70 | 8 | 0,50 | 0,50 | AV70 8/0-0,5 |
| 45 | 8 | 1,00 | 1,00 | AV45 8/0-1 |
| 70 | 8 | 1,00 | 1,00 | AV70 8/0-1 |
| 45 | 10 | 0,50 | 0,50 | AV45 10/0-0,5 |
| 70 | 10 | 0,50 | 0,50 | AV70 10/0-0,5 |
| 45 | 10 | 1,00 | 1,00 | AV45 10/0-1 |
| 70 | 10 | 1,00 | 1,00 | AV70 10/0-1 |