

Tlaková hadice pro pohonné hmoty, T654 AA, -40°C/+125°C

// 654AA **NEW**



EVOLUTION

**Multi-fuel 20 bar (300 psi)
SAE J30R7**

Tube: black conductive NBR.

Reinforcement: high tensile textile cords.

Cover: black conductive CR - abrasion, ozone and hydrocarbon resistant.

Application: fuel and oil delivery.

Also suitable for automotive and marine fuel transfer.

Constant operation: -40 °C +125 °C (-40 °F +257 °F)

↔		↔		↻		↻		⌒		⚡	⚖	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft
6,0	1/4"	12,00	0,47	20	300	60	900				0,110	0,08
8,0	5/16"	14,00	0,55	20	300	60	900				0,130	0,09
10,0	3/8"	16,00	0,63	20	300	60	900				0,160	0,11
13,0	1/2"	20,00	0,79	20	300	60	900				0,220	0,15
16,0	5/8"	24,00	0,94	20	300	60	900				0,300	0,21
19,0	3/4"	27,00	1,06	20	300	60	900				0,330	0,23
25,0	1"	34,00	1,34	20	300	60	900				0,220	0,15