

# GUMEX

// 340AH



EXTRUDED  
TUBE

## Steam 18 bar (270 psi) - Steel braided

**Tube:** black conductive EPDM.

**Reinforcement:** one or two high tensile steel wire braids.

**Cover:** red EPDM - heat, abrasion and ozone resistant - pin pricked.

**Application:** saturated and superheated steam.

**Constant operation:** -40 °C +210 °C (-40 °F +410 °F)  
intermittent to 232 °C (450 °F)

⊖		⊖		⊖		⊖		⊖		⊖		⊖	
mm	in	mm	in	bar	psi	bar	psi	mm	in	%	kg/m	lb/ft	
13,0	1/2"	23,00	0,91	18	270	180	2610	130,0	5,12		0,400	0,27	
16,0	5/8"	26,00	1,02	18	270	180	2610	160,0	6,30		0,480	0,33	
19,0	3/4"	31,00	1,22	18	270	180	2610	190,0	7,48		0,740	0,50	
25,0	1"	38,00	1,50	18	270	180	2610	250,0	9,84		0,900	0,61	
32,0	1 1/4"	46,00	1,81	18	270	180	2610	320,0	12,60		1,190	0,80	
38,0	1 1/2"	52,00	2,05	18	270	180	2610	380,0	14,96		1,340	0,91	
51,0	2"	67,00	2,64	18	270	180	2610	510,0	20,08		2,130	1,44	
63,0	2 1/2"	81,00	3,19	18	270	180	2610	630,0	24,80		2,990	2,01	
76,0	3"	94,00	3,70	18	270	180	2610	760,0	29,92		3,970	2,67	