



DATA SHEET

SHILTEK LG™ FIRE RESISTANCE SLEEVINGS

COLOUR	ORANGE / RED	
COMPOSITION	FIBER GLASS COATED WITH SILICONE	
CONTINUOUS WORKING TEMPERATURE	from -54 °C to + 260°C from -65°F to 500°F	
CHEMICAL RESISTANCES	ACETONE	GOOD
	ACETIC ACID	POOR
	HYDROCHLORIC ACID	POOR
	NITRIC ACID	NOT RESISTANCE
	SUPHURIC ACID	NOT RESISTANCE
	HYDROGEN DIOXIDE 10%	POOR
	HYDROGEN DIOXIDE 20%	VERY POOR
	GLYCOL	GOOS
	FUEL	VERY GOOD
	FUEL DIESEL	VERY GOOD
	KEROSENE	VERY GOOD
	ETHYL ALCOHOL	GOOD
	FREON F 22 LIQUID	POOR
	METHANE	VERY GOOD
	METHYL ALCOHOL	VERY GOOD
	METILEILKETONE	VERY GOOD
	HYDRAULIC OIL	VERY GOOD
	MINERAL OIL	VERY GOOD
MOTOR OIL	VERY GOOD	
PETROLEUM	VERY GOOD	
UV RESISTANCE		VERY GOOD

ed. July 2017